Sanitized Copy Approved for Release 2010/07/14 : CIA-RDP80T00246A041100390001-2 🛛 🦝 🥱

INFORMATION REPORT INFORMATION REPOR

CENTRAL INTELLIGENCE AGENCY

PROCESSING COPY

This material contains information affecting the National Defense of the United States 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner was

the meaning of the Fspionage Laws, It

		SallaCalla lia	Т.	and the state of t	25X1
COUNTRY	East Germany		REPORT		
SUBJECT	VEB Chemische Werke Bu Products and Industric Products		DATE DISTR.	1.7 MAT 1998	ę
			REFERENCES		1 41
DATE OF INFO. PLACE &					25X1
DATE ACQ.					
	SOURCE EVALUATIONS	ARE DEFINITIVE. APPRA	AISAL OF CONTE	NT IS TENTATIVE.	7
â	General General			a.	- > 4/25X1
1.	During the past few yea Schkopau, has been alto the individual producir makes it ever more diff A system of pipelines w	ered in such a way ng sections are mu ficult to put newl	that, in the tually inter- y-developed	e flow of produc dependent. This products into pr	oduction.

2. However, since the alteration of the factory took place one of the biggest difficulties in the way of a normal flow of production has been the lack of an assured supply of raw materials and of sufficient reserves of raw materials. Furthermore, the rate of replacement of parts for machinery which was obtained from the West is unsatisfactory and this causes difficulties.

Products Being Developed as of July 1957

the products of one section on to the next one, etc.

- 3. As of July 1957 the following products were being developed at VEB Chemische Werke Buna, Schkopau:
 - a. Buna S 4 T: a plastic synthetic rubher with high impulse resistance.

 Its principal application will be in the manufacture of tires, cable, hose and conveyor belts.
 - b. Epoxide resin: a solvent-free adhesive which hardens with the addition of hardeners and under the influence of heat without any loss of substance.
 - c. <u>Varnish raw material (Lackrohstoff) PVJ (?)</u>: a varnish binding agent which is suitable for rust protection and other special-purpose varnish uses. This product can be combined with various other varnish raw materials.

							5- E- C-	R-E-T					1	
													4/1	25X1
STATE	x	ARMY	x	NAVY	х	AIR	x	FBI	AEC	ORR	Ev	x		1
				11 ///	r: () d: A	theat - Le	### X							
(Note: Wa	shington	distributio	n indicate	a by "A";	LIGIO GIST	ribution by	# 1							3

NFORMATION REPORT INFORMATION REPORT



S-E-C-R-E-T 25X1

- d. Polyvinyl alcohol Schkopau 80: a polyvinyl alcohol of an especially high degree of polymerization; especially suitable for the optical industry.
- e. <u>PVC-SP Schkopau:</u> a suspension of polymeride which is practically nonwaterabsorbing and of great value for the electrical industry, especially for the manufacture of high-grade cable and transparent foils.
- f. Vinalit SP 80: a Perlon polymeride (Perlpolymerisat) of vinyl acetate with a high K value. It differs from Vinalit SP 60 in having a higher fusing temperature.
- g. Polyester: a casting resin (Gussharz) for the manufacture even of large parts without using presses and with small tool cost. In combination with glass and other fibers, very high mechanical characteristics are achieved.
- h. Polyethylene: the well-known injection die-casting material (Spritzguss-material) with capabilities for universal processing and application: for example, flexible foils, cable, rust protection and numerous products for use in daily life.
- 4. The following is a list of the products of VEB Chemische Werke Buna, Schkopau, arranged according to types of products:

a. Synthetic rubber:

	S 3 Band	Buna	SO 40
Buna	S 3 Krumel (lump)	Buna	85
	SS 3 Band		N Band
Buna	SS 3 Krumel	Buna	N Krümel
Buna	S 4	Buna	NN Band
Buna	S 4 L	Buna	NN Krumel
Buna	S 4 T	Buna	NW

b. Plastics:

PVC Schkopau,	type F	PVC-SP Schkopau
PVC Schkopau,	type GN	Polyacrilnitril
PVC Schkopau,	type G	Polyamid AH Schkopau
PVC Schkopau,	type J/F	Polystyrol BW, transparent
PVC Schkopau,	type J/G	Polystyrol EF
PVC Schkopau,	type J/GN	Polystyrol EFS
PVC Schkopau,	type K	Polyvinyl alcohol Schkopau
PVC Schkopau,	type P	Plastic lead seal substance (Kunststoffplombenmasse)
PVC Schkopau,	type R	Injection die-casting substance (Spritzgussmasse) K

c. Buna and Plastic Latices:

Acrylit DA, approximately 40%
Acrylit DAS, approximately 40%
Bunalatex S 3 special, approximately 35%
Bunalatex S 3 35%
Bunalatex SS special, approximately 50%
Vinalit D 50
Vinalit DC 39/20
Vinalit DC 44/11
Vinitex, approximately 50%

S-E-C-R-E-T					

25X1

S-E-C-R-E-T 25X1

d. Additives:

Stabilizer L Thickener AN

e. Adhesive Resins and Varnish Binding Agents:

Acrylit L
Chlorbuna M
Pervinan 100 %
Pervinan, approximately 80%,
in toluol
Vinalit LE 60/40%

Phthalopal BU
Rubresin B
Vinalit SP 60
Vinalit LE, 40/60%
Vinalit MPS

f. Solvents:

Acetone, chemically pure
Ethyl acetate 98/100 %
Ethyl acetate, approximately 75%
Ethylene chloride, distilled
Ethyl glycol
Butanol
Butyl acetate 85%
Butyl butyrate

Dioxane
Isopropanol
Solvent B 17
Methyl acetate
Perchlorethylene
Reintuol
Trichlorethylene
Butyl butyrate

g. Softeners for Plastic Substances and Plasticizers for Rubber Mixtures:

Palatinol AH Plasticizer FON
Palatinol C Plasticizer RA
Plasticizer 32

h. Synthetic Oils:

Transmission oil Motor oil 50 Mot. 12
Refrigerator oil Motor oil 50 Mot. 15
Motor oil 50 Mot. T
Motor oil 50 Mot. 10

i. Products for Treating and Finishing Textiles:

Appretex AW Diazopal O Appretex A Diazopal O, concentrated Emulsifier MF, soluble in oil Appretex W Appretex c Fluval L, highly concentrated Bunalatex SS special, approximately 50% Lychromal A Bunalatex S 3, approximately 35% Lychromal D Bunalatex S 3 special, approximately 35% Nekal BX, dry Peral O, highly concentrated Peral 0 Seral NT Polyvinyl alcohol Schkopau Seral FK Sapal L, concentrated Seral M Paste Seral S Sapal W, highly concentrated Stabilizer L

Thickener AN

S-E-C-R-E-T	
	25X1

S-E-C-R-E-T

j. Glycerin-Substitute Products (for technical purposes)

Glycol Diglycol Hexantriol, technical Triglycol

k. Miscellaneous:

Recovered sulfuric acid Acetoacetic ester Ethyl benzol Aluminum chloride, anhydrous, containing iron and technically free of iron Ethylene chlorhydrine, 98/100% Caustic soda lye, approximately 45% Construction lime (carbide lime hydrate) Brake fluid, blue Ethyl chloride, technically pure Ethyl chloride DAB VI Methyl chloride Dispersal P Dispersal EP Dispersal WS Lime powder (carbide lime hydrate) Triaethanolamin, distilled

Erkalen- Neu, in solution
Acetic acid, chemically pure,
approximately 80%
Acetic acid, chemically pure,
approximately 98/100%
Acetic acid, technically pure,
approximately 98/100%
Acetic acid annivaride
Formaldehyde, 30 Gew.% (sic)
Glysantin
Kalunit, liquid, N

Industrial lime (carbide lime hydrate)
Chloracetic acid
Phthalopal G
Phthalic acid anhydride, pure, in
flakes
Pure benzol
Sintering lime
Oxide wax (Oxydwachs) AN

Triaethanolamin, technical

25X1

S-E-C-R-E-T

25X1

′25X1

Sanitized Copy Approved for Release 2010/07/14 : CIA-RDP80T00246A041100390001-2 25X1

